

MODEL F 80 to 180 C.V.

Reinforced chassis and turret with optional hydraulic ridgers or rollers.

Reinforced oil-tight cutting edges, with axial joints.

Revolutions and characteristics adapted to each tractor.

Centred with Nodular casting crankcase and group.

Includes reinforced drive with safety clutch.

Rear curved collector for higher definition.

6 blades per disc, bolts and pins.

Reinforced lateral gear drive.

Tractors with maximum shaft height of 70 cm.



MODEL	N° OF BLADES	CUT WIDTH	TOTAL WIDTH	MAX POWER	WEIGHT
F-45	45	2.049	2.177	80 - 180	905
F-48	48	2.173	2.301	90 - 180	915
F-51	51	2.312	2.440	100 - 180	955
F-54	54	2.436	2.564	110 - 180	975
F-57	57	2.575	2.703	115 - 180	1.005
F-60	60	2.699	2.827	120 - 180	1.025
F-63	63	2.838	2.963	125 - 180	1.055
F-66	66	2.962	3.092	130 - 180	1.075

OPTIONS:

CODE	DESCRIPTION
01020	FOLDABLE MECHANICAL FLAPS
1062	FOLDABLE HYDRAULIC FLAPS
01000	SPLINED TRANSMISSION
01186	TRANSMISSION WITH TORQUE LIMITER
01010	SPLIT HORIZONTAL COLLECTOR
Z1323	FLAP COVERS AND STAINLESS STEEL COLLECTOR
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE
01164	STRAIGHT BLADE (4 PER SQUARED DISC)
4/DISCO	4 BLADES/DISC FOR "FANGUEO" (RICE)