

TM SELF-FED SHREDDER (REAR) WOOD 75 to 160 H.P.

TECHNICAL CHARACTERISTICS

- Total working # width of just 17.5cm Singular transmission only lateral
- 8 mm shell and lateral sections with 10mm structural reinforcements.
- Includes free wheel drive, bolts and pins.
- Reversible hydraulic feeding pump.
- Self-fed for rocky or tilled land.
- 480 mm rotor diameter.
- 2 automatic tensioners, in feeder and rotor.
- Twin reinforced feeder chain.
- Flow controller (as standard)
- 220 mm rear roller vibration reducer.
- Double row auto-oscillating barrel bearings.
- With roller feeder. For all types of tractors.
- Shredding capacity up to 16cm in diameter.
- Casting rotor-bearing supports.
- Special wood shredder, with high capacity shredding.
- Comes with hammers, crumbling saws and counter-saws.



MODEL	Nº OF BLADES/ HAMMERS	CUT WIDTH MM.	TOTAL WIDTH MM.	MAX POWER H.P.	WEIGHT KG
TM-150	32/16	1,500	1,675	75 - 160	1.150
TM-175	40/20	1,750	1,925	85 - 160	1.270
TM-200	48/24	2,000	2,175	95 - 160	1.390

Options:

CODE	DESCRIPTION
01108	CYLINDER REF. WITH HOSES AND VALVE
01120	CYLINDER REF. LONG WITH HOSES AND VALVE
Y610	VISOR AND SIDE (cutting width +18 cm)
01193	REAR MECHANIC WHEELS (NO ROLLER)
66255	G9 REINFORCED TRANSMISSION
70038	ROTOR EAR REINFORCEMENTS