

VMS ROTOTILLER 35 to 90 H.P.

TECHNICAL CHARACTERISTICS

- Reinforced gears lateral drive.
- Nodular casting crankcase and group.
- Includes reinforced drive with safety clutch.
- 6 blades per disc, bolts and pins.
- Centred or displaced, to be advised when ordering.
- Rear curved collector for higher definition.
- Revolutions and characteristics adapted to each tractor.
- For fruit or vine tractors.



MODEL	Nº OF BLADES	CUT WIDTH MM.	TOTAL WIDTH MM.	MAX POWER H.P.	WEIGHT KG.
VMS-24	24	1,070	1,230	35 - 80	450
VMS-27	27	1,226	1,386	40 - 80	465
VMS-30	30	1,325	1,485	40 - 80	485
VMS-33	33	1,481	1,641	45 - 80	515
VMS-36	36	1,580	1,740	45 - 80	531
VMS-39	39	1,736	1,896	50 - 80	550
VMS-42	42	1,835	1,995	50 - 80	561
VMS-45	45	1,991	2,151	60 - 80	595
VMS-48	48	2,090	2,250	60 - 80	610

Options:

CODE	DESCRIPTION
01020	FOLDABLE MECHANICAL FLAPS
01062	FOLDABLE HYDRAULIC FLAPS
01010	SPLIT HORIZONTAL COLLECTOR
01031	RIGHT SIDE GRILLE
C / D	CENTRED OR DISPLACED