

PSR ROTOTILLER 60 to 130 H.P.

TECHNICAL CHARACTERISTICS

- Revolutions and characteristics adapted to each tractor.
- Reinforced lateral gear drive.
- Nodular casting crankcase and group.
- For maximum shaft height of 65cm.
- Up to 80cm gearbox optional.
- 6 blades per disc, bolts and pins.
- Medium power standard tractors.
- Includes reinforced drive with safety clutch.
- Rear curved collector and shell for higher definition.



MODEL	Nº OF BLADES	CUT WIDTH MM.	TOTAL WIDTH MM.	MAX POWER H.P.	WEIGHT KG.
PSR-36	36	1,610	1,800	60 - 130	640
PSR-39	39	1,774	1,964	65 - 130	670
PSR-42	42	1,873	2,063	70 - 130	700
PSR-45	45	2,037	2,227	75 - 130	730
PSR-48	48	2,136	2,326	80 - 130	760
PSR-51	51	2,300	2,490	90 - 130	790
PSR-54	54	2,399	2,589	100 - 130	820
PSR-57	57	2,563	2,753	110 - 130	860
PSR-60	60	2,662	2,852	120 - 130	900

Options:

CODE	DESCRIPTION
14510	FOLDABLE MECHANICAL FLAPS 450 mm
14613	FOLDABLE HYDRAULIC FLAPS 450 mm
01000	SPLINED TRANSMISSION
01186	TRANSMISSION WITH TORQUE LIMITER
01010	SPLIT HORIZONTAL COLLECTOR
10020	2 SPEED STICK SHIFT GEARBOX
02009	1 SPEED STICK SHIFT GEARBOX (FS MODEL)
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE