

F ROTOTILLER 80 to 180 H.P.

TECHNICAL CHARACTERISTICS

- Reinforced chassis and turret with optional hydraulic ridgers or rollers.
- Reinforced oil-tight cutting edges, with axial joints.
- Revolutions and characteristics adapted to each tractor.
- Centred with Nodular casting crankcase and group.
- Includes reinforced drive with safety clutch.
- Rear curved collector for higher definition.
- 6 blades per disc, bolts and pins.
- Reinforced lateral gear drive.
- Tractors with maximum shaft height of 75 cm.



MODEL	Nº OF BLADES	CUT WIDTH MM.	TOTAL WIDTH MM.	MAX POWER H.P.	WEIGHT KG.
F-39	39	1,786	1,914	75 - 180	835
F-42	42	1,910	2,038	75 - 180	875
F-45	45	2,049	2,177	80 - 180	915
F-48	48	2,173	2,301	90 - 180	985
F-51	51	2,312	2,440	100 - 180	1.035
F-54	54	2,436	2,564	110 - 180	1.085
F-57	57	2,575	2,703	115 - 180	1.135
F-60	60	2,699	2,827	120 - 180	1.185
F-63	63	2,838	2,963	125 - 180	1.235
F-66	66	2,962	3,092	130 - 180	1.285

Options:

CODE	DESCRIPTION
14510	FOLDABLE MECHANICAL FLAPS 450 mm
14613	FOLDABLE HYDRAULIC FLAPS 450 mm
01000	SPLINED TRANSMISSION
01186	TRANSMISSION WITH TORQUE LIMITER
01010	SPLIT HORIZONTAL COLLECTOR
Z1323	FLAP COVERS AND STAINLESS STEEL COLLECTOR
00536	SHELL LINED IN STAINLESS STEEL
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE
01164	STRAIGHT BLADE (4 PER SQUARED DISC)
10512	SIDE DISC SET
4/DISCO	4 BLADES/DISC FOR "FANGUEO" (RICE)