

FS ROTOTILLER 80 to 180 H.P.

TECHNICAL CHARACTERISTICS

- Reinforced chassis and turret with optional hydraulic ridgers or rollers.
- Reinforced oil-tight cutting edges, with axial joints.
- Revolutions and characteristics adapted to each tractor.
- Centred with Nodular casting crankcase and group.
- Includes reinforced transmission with torque limiter
- Rear curved collector for higher definition.
- 6 blades per disc, bolts and pins.
- Reinforced lateral gear drive.
- Tractors with maximum shaft height of 85cm.
- With 1 speed high group for raised shaft.



MODEL	Nº OF BLADES	CUT WIDTH MM.	TOTAL WIDTH MM.	MAX POWER H.P.	WEIGHT KG.
FS-45	45	2,049	2,177	80 - 180	1000
FS-48	48	2,173	2,301	90 - 180	1.050
FS-51	51	2,312	2,440	100 - 180	1100
FS-54	54	2,436	2,564	110 - 180	1150
FS-57	57	2,575	2,703	115 - 180	1200
FS-60	60	2,699	2,827	120 - 180	1250
FS-63	63	2,838	2,963	125 - 180	1300
FS-66	66	2,962	3,092	130 - 180	1350
FS-69	69	3.101	3.229	140 - 180	1400
FS-72	72	3.225	3.353	150 - 180	1450

Options:

CODE	DESCRIPTION
14510	FOLDABLE MECHANICAL FLAPS 450 mm
14613	FOLDABLE HYDRAULIC FLAPS 450 mm
01000	SPLINED TRANSMISSION
01010	SPLIT HORIZONTAL COLLECTOR
Z1323	FLAP COVERS AND STAINLESS STEEL COLLECTOR
00536	SHELL LINED IN STAINLESS STEEL
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE
01164	STRAIGHT BLADE (4 PER SQUARED DISC)
10512	SIDE DISC SET
4/DISCO	4 BLADES/DISC FOR "FANGUEO" (RICE)